

ZR-420Y/520Y

全自动硬盒真空调包装机


Fully Automatic Hard Box Vacuum Modified Atmosphere Packaging Machine




适用物料: 卤蛋, 水滴蛋、辣条等。
Applicable Materials: Soy egg, Dried Eggs, Spicy Sticks, etc.



单面成型局部
Single sided forming part



激光刀模整版冲
Laser knife mold full plate punching



错位整版冲
Misalignment full page printing

Scope of Use 使用范围

适用于对各种食品, 鱼豆腐、单粒豆干, 双粒豆干、槟榔、麻辣食品、肉制品、海产品、果蔬、酱菜、冷却肉、医药产品、五金元件、医疗器械等进行真空、充气、贴体包装。

It is suitable for vacuum, inflatable and body fitted packaging of various foods, such as fish tofu, single dried tofu, double dried tofu, areca, spicy food, meat products, seafood, fruits and vegetables, Pickled vegetables, chilled meat, pharmaceutical products, hardware components, medical devices, etc.

Performance Characteristics 性能特点

- 三菱PLC电脑控制系统(高配置), 大型真彩彩色人机界面触屏控制屏推拉式设计;
- 日本安川伺服电机控制高速、高精度步进走速;
- 温度电脑控制系统, 智能加热功能, 水冷精确控温;
- 进口光电对标(德国斯克)跟踪系统, 可用彩盖膜, 保证图案位置对正;
- 果用德国原装BUSCH RA0202D型环保真空泵, 真空力度大, 真空度高;
- 德国威特(WITT)刀气混配仪保证气调产品质量和安装;
- 日本进口异性刀模保证产品外观美观大方;
- 气动元件所有电磁阀果用日本SMC气动系统;
- 伺服牵引果用意大利进口缝条(雷吉纳);
- 组合封口模具, 整体封口垫子(德国进口硅胶);
- 进口电气元件;
- 上、下膜采用左右纠偏功能、自动送膜和涨紧系统;
- 多种废料回收系统(丝杆往复式、整版收腹式)。

- Mitsubishi PLC computer control system (high configuration), large true color human-machine interface touch screen control screen push-pull design;
- Japan's Yaskawa servo motor controls high-speed and high-precision stepping speed;
- Temperature computer control system, intelligent heating function, precise water cooling temperature control;
- The imported photoelectric benchmarking (German Sk) tracking system can use color cover film to ensure the alignment of the pattern position;
- Use the German original BUSCH RA0202D environmentally friendly vacuum pump, which has a strong vacuum force and high vacuum degree;
- Germany's WITT knife gas mixer ensures the quality and installation of gas controlled products;
- Japanese imported foreign knife molds ensure the appearance of the product is beautiful and elegant;
- All solenoid valves of pneumatic components shall be equipped with Japanese SMC pneumatic system;
- Servo traction fruit with Italian imported seam strips (Reggina sodium);
- Combination sealing mold, integral sealing pad (imported silicone from Germany);
- Imported electrical components;
- The upper and lower membranes adopt left and right deviation correction functions, automatic film feeding and tightening systems;
- Various waste recycling systems (screw reciprocating, full plate belly retraction).

Product Technical Parameters 产品技术参数

型号	Model	ZR-420Y	ZR-520Y
上膜宽	Width of upper film	398mm	498mm
下膜宽	Widet of lower film	423mm	523mm
真空度	Vacuum	≤200Pa	≤200Pa
压缩空气	Compressed air	≥0.6Mpa	≥0.6Mpa
耗气量	Gas consumption	≥0.6m³/min	≥0.6m³/min
充入气体压力	Fill up gas pressure	≥0.2Mpa	≥0.2Mpa
速度	Speed	4-6p/min	4-6p/min
充气接口	Fill up gos join	Φ16PU tube	Φ16PU tube
冷却水	Cooling water	≥0.15Mpa	≥0.15Mpa
电源	Power	380V/50HZ	380V/50HZ
总功率	Capacity	12-18kw	12-18kw
外型尺寸	Dimensions	8000×1085×2000mm	8000×1185×2000mm
整机重量	Total weight	2250kg	2450kg